

## LED OMNIDIRECTIONAL A19 3-WAY SERIES



### PRODUCT DESCRIPTION:

MaxLite's LED 3-way Lamp offers three distinct levels of light to suit any task or mood. For use in standard 3-way fixtures, the LED lamps replicate the beautiful, warm light of an incandescent bulb while consuming 86 percent less energy and lasting 25 times longer.

### FEATURES:

- Input Wattage: 4W/8W/14W
- Replacement for 40W/60W/100W Incandescent
- Lumens: 500/1000/1500
- CCT: 2700K & 3000K, 5000K
- CRI: ≥81
- ENERGY STAR certified for 3000K and 5000K models
- For use in 3-way light fixtures (non-dimmable)
- 300° beam angle
- Power factor: ≥ 0.90
- Standard E26 base
- Not for use in totally enclosed luminaires
- Suitable for damp locations
- 25,000 Hour life (L70 standards)

### APPLICATIONS:

- Table and floor lamps
- Pendants

### WARRANTY:

1-year standard warranty  
(further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))

#### MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: 14A19/3W27

14A19/3W		
FAMILY	BASE	CCT
14A19/3W= 14 watts, A19, 3-Way	(OMIT)= E26	27= 2700K 30= 3000K 50= 5000K

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including interference that may cause undesired operation.

**SPECIFICATIONS:**

**14A19/3Wxx**

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Power Consumption	4W/8W/14W
	Lumens Delivered	500/1000/1500
	CRI	≥81
	Color Temperature (CCT)	2700K, 3000K, 5000K
	Lumen Maintenance (L70)	25,000 Hours
ELECTRICAL	Power Factor	≥0.90
	Input Voltage	120V
PHYSICAL	Base Type	E26
	Operating Temperature	-4°F - 104°F
CERTIFICATION	Certification	cULus Listed, RoHS compliant
	Environment	Dry, Damp
	Warranty	1 year standard warranty

**ORDERING:**

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	CRI	DIMENSIONS (W" x MOL")	CCT
101528	14A19/3W27		4W/8W/14W	40/60/100W Inc.	500/1000/1500	81	2.36" x 4.60"	2700K
102295	14A19/3W30	★				84		3000K
102562	14A19/3W50	★				84		5000K

★ ENERGY STAR certified