

LED SUNSET BR LAMP
BR30 SUNSET SERIES



PRODUCT DESCRIPTION:

Unlike standard LED lamps, which remain the same color temperature as they dim, the warm-on-dim BR30 mimics the smooth dimming performance of incandescent and halogen bulbs by decreasing in color temperature as light output is lowered. The color of the lamp subtly shifts from 3000K to 2200K as it dims to 10 percent of full light output to create a warm, inviting glow for dining, entertaining or relaxing. Designed for use in recessed lights, the 9-watt lamp produces 650 lumens of beautiful, even illumination using 86 percent less energy than the 65-watt incandescent lamp it is meant to replace.

FEATURES:

- 9W
- 650 lumens
- 72 lumens per watts
- CCT: 3000K
- ENERGY STAR Certified
- Instant on
- 25,000 hour life (L70 standards)
- CRI: 85
- Dimmable down to 10 percent
- Warm-on-dim 3000K-2200K
- Saves more than 86 percent on energy
- Power factor: ≥ 0.9
- Standard E26 base
- Mercury and lead free
- 1 year standard warranty

APPLICATIONS

- Recessed lighting
- Decorative lightings
- Not for use in fully enclosed luminaires
- Not for use with emergency lighting
- Suitable for use in damp locations

WARRANTY:

1-year standard warranty
(further details available at www.maxlite.com/warranties)

ORDERING:

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 9BR30SDLED30	
9BR30S		SDLED	30
FAMILY	BASE	DIMMABILITY	CCT
9BR30S= 9 watts, BR30 Sunset	(OMIT)= E26	SDLED= Dimmable	30= 3000K

NOTES:

1. Compatible dimmer list is located on page 3.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference.
- (2) This device must accept any interference received, including interference that may cause undesired operation.

SPECIFICATIONS:

9BR30SDLED30

ITEM	SPECIFICATION	DETAILS
GENERAL PERFORMANCE	Power Consumption	9W
	Lumens Delivered	650
	Efficacy (lm/w)	72
	CRI	85
	Color Temperature (CCT)	3000K
	Lumen Maintenance (L70)	25,000 Hours
	Use in Totally Enclosed Luminaires	No
ELECTRICAL	Power Factor	≥0.9
	Input Voltage	120V
	Frequency	60Hz
	Current (A)	≥0.08
PHYSICAL	Base Type	E26
	Operating Temperature	-4°F - 104°F
CERTIFICATION	Environment	Dry, Damp
	Warranty	1 year standard warranty

Lighting layouts and spacing criteria available upon request

ORDERING:

ORDER CODE	MODEL	WATTS	EQUIVALENCY	OUTPUT (LUMENS)	EFFICACY (lm/W)	CRI	DIMENSIONS (D" x MOL")	CCT
E26 Base								
101363	9BR30SDLED30	9	65W Inc.	650	72	85	3.75" x 5.16"	3000K

COMPATIBLE DIMMERS

BRAND	FAMILY	MODEL#	COMPATIBILITY
LEVITON	Sureslide	06674-POB	✓
	Sureslide	06672-1LT	✓
	Sureslide	06631-1LT	✓
	Sureslide	06633-PLI	✓
	Vizia	VPI06-1LZ	✓
	Sureslide	R62-06674-POW	✓
	Sureslide	R60-06681-0IW	✓
	Sureslide	6613-P	✓
LUTRON	Diva	DVCL-153P	✓
	Maestro	MACL-153M	✓
	Credenza	TTCL-100H	✓
	Contour	CT-600P	✓
	Diva	DVLV-600P	✓
	Contour	CTCL-153PDH-WH	✓
	Skylark	S-600P-WH	✓
	Skylark	SLV-600P-WH	✓
PASS & SEYMOUR	Legend Harmony	DCL453PTCCCV6	✓
	Legend Harmony	HCL453P	✓
	Legend Harmony	H703PTCCV6	✗

✓ COMPATIBLE
✗ NOT COMPATIBLE