

CFL MINIBULB



With the same familiar shape and small size of incandescent bulbs, MaxLite's CFL MiniBulbs save up to 75 percent in energy by replacing incandescent bulbs ranging from 25- to 60-watts, using just 7- to 18-watts. Ideal for table, desk and floor lamps, recessed lighting, wall sconces, ceiling mounted lighting and other corridor lighting fixtures in homes, offices, restaurants, schools, hospitals, and retail and hospitality applications, the CFL MiniBulbs are available in 2700K (soft white), 4100K (cool white) and 5000K (daylight) correlated color temperatures (CCT).

| |
|----------------|
| PROJECT NAME |
| CATALOG NUMBER |
| NOTES |
| FIXTURE TYPE |

FEATURES:

- Saves up to 75 percent energy costs
- Soft natural light with excellent color rendering
- Familiar incandescent shape and small size fits most fixtures
- Rapid start electronic ballast with flicker-free operation
- High color rendering index (CRI) of ≥ 80 for crisp, clear color
- E26 (Edison) or E12 (candelabra) bases available

SPECIFICATION:

- Ballast Type: Electronic
- Starting Method: Instant Start
- Input Line Voltage: 120VAC
- Input Line Frequency: 50/60HZ
- Min. Starting Temp.: 0°F
- Max. Operating Temp.: 100°F
- CRI: ≥ 80

SPECIAL NOTES:

- Do not use with dimmers or other control devices
- Suitable for indoor use
- Fits most household fixtures
- Same size as an incandescent A19



SKB7EAWW-107

SKB7EAWW



SKB11EA

SKB13EA

SKB18EAWW

SKB20EAWW

Lamp Ordering Information:

| Watts | Order Code | Model Number | Incandescent Equivalent | Lumens | Pack Type | Life (Hrs.) | Dimensions (W" x MOL") | CCT |
|-------|------------|---------------|-------------------------|--------|-----------|-------------|------------------------|-------|
| 7 | 31131 | SKB7EAWW | 25 | 450 | Box | 10,000 | 2.4" x 4.2" | 2700K |
| 7 | 75480 | SKB7EAWW-107 | 25 | 310 | Box | 10,000 | 2.4" x 4.2" | 2700K |
| 13 | 31533 | SKB13EAWW-107 | 60 | 800 | Box | 10,000 | 2.4" x 4.85" | 2700K |
| 13 | 70666 | SKB13EAPWW | 60 | 800 | Box | 15,000 | 2.4" x 4.3" | 2700K |
| 13 | 31535 | SKB13EAPCW | 60 | 800 | Box | 15,000 | 2.4" x 4.3" | 4100K |
| 13 | 31534 | SKB13EAPDL | 60 | 800 | Box | 15,000 | 2.4" x 4.3" | 5000K |
| 18 | 72123 | SKB18EAWW | 75 | 1150 | Box | 10,000 | 2.6" x 5.08" | 2700K |
| 20 | 70013 | SKB20EAWW | 60 | 1,050 | Box | 10,000 | 2.65" x 2.70" | 2700K |



This device complies with Part 18 of the FCC rules. If interference occurs move this product away from the device or plug into a different outlet. This product may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating between 0.45-30MHz.



MAX11211