

CEILING FLUSH MOUNT

LED INTEGRATED




PUFF



ARCHITECTURAL



SLIM



DISC/FAUX CAN



TRADITIONAL



PEARL



PRODUCT DESCRIPTION:

LED Flush Mount Ceiling Fixtures provide exceptional performance in general lighting applications for residential, multi-unit residential, hotels, and commercial properties. Built with an integrated LED panel, MaxLite flush mounts produce a high quality of light with superior longevity and energy savings when compared to traditional sources. The series is available in nickel, white or bronze finishes with a high-transmission glass lens to complement virtually any décor.

FEATURES:

- ETL listed for damp locations
- Voltage / Frequency: 120V, Triac Dimming, 60Hz
- CRI: ≥80 or ≥90 available
- Operating temperature: -4°F to 104°F (-20°C to 40°C)
- Rated Life: L70 ≥50,000 Hours
- Construction: Die formed steel
- Powder coat finish

WARRANTY:

5-year standard warranty* (further details available at www.maxlite.com/warranties)

*Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

PUFF



WATTAGE	14W	18W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1220	1440	1950
Efficacy (lm/W @ 2700K, 80CRI)	95	80	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1408691	ML2LAMPWH18827
100703	ML2LALPWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATT-AGE	CRI	CCT	OPTIONS
ML2=Ceiling Flush Mounts	LA=LED Integrated	S=Small, 11" D x 4.0" H ¹	P=Puff	WH=White	[BLANK]=120V Triac dimming	14=14W	8=80CRI 9=90CRI ¹	27=2700K 30=3000K	J=JA8 Compliant ²
		M=Medium, 13" D x 4.0" H				18=18W			
		L=Large, 16" D x 4.0" H				24=24W			

¹ Consult factory for lead times and order quantities

² JA8 compliance available in 90CRI, 14W, 11"D x 3.15"H model only. Consult factory for lead time and order quantities.

ARCHITECTURAL



WATTAGE	16W	22W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1300	1600	1950
Efficacy (lm/W @ 2700K, 80CRI)	82	73	81

STOCKED ITEM	
ORDER CODE	CATALOG NUMBER
1410232	ML2LAMABN22830
1409612	ML2LALABN24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2=Ceiling Flush Mounts	LA=LED Integrated	S=Small, 11.9" D x 3.3"H ¹	A=Architectural	BN=Brushed Nickel	[BLANK]=120V Triac dimming	16=16W	8=80CRI 9=90CRI ¹	27=2700K ¹ 30=3000K
		M=Medium, 14.2" D x 3.5"H				22=22W		
		L=Large, 16.1"D x 4.3"H				24=24W		

¹ Consult factory for lead times and order quantities

SLIM




WATTAGE	12W	15W	24W
Sourced lumen (lm @ 3000K, 80CRI)	875	1054	1650
Efficacy (lm/W @ 3000K, 80CRI)	70	70	69

STOCKED ITEMS	
ORDER CODE	CATALOG NUMBER
1410130	ML2L11SLN1230
1410132	ML2L13SLN1530
1410134	ML2L15SLN2430

FAMILY	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CCT
ML2L=Ceiling Flush Mount	11=11", 11.0 D x 1"H	SL=Slim	Ni=Nickel	[BLANK]=120V Triac dimming	12=12W	30=3000K
	13=13", 13.0 D x 1"H		WH=White		15=15W	
	15=15", 14.9"D x 1"H		24=24W			

DISC/ FAUX CAN



SIZE	4"	6"	7"
Delivered lumen (lm @ 2700K, 80CRI)	631	950	1050
Efficacy (lm/W @ 2700K, 80CRI)	69	85	70

STOCKED ITEM			
ORDER CODE		CATALOG NUMBER	
14099586		DL409830WH	
14099588	14099589	14099590	DL6158(27 30 40)WH
14101759	14101760	14101761	DL7158(27 30 40)WH

FAMILY	SIZE	VOLTAGE	WATTAGE	CRI	CCT	FINISH
DL=Disc Light	4=4", 4.92" D x 1.33"H	[BLANK]=120V Triac dimming	09=9W	8=80CRI	27=2700K 30=3000K 40=4000K	WH=White
	6=6", 5.90"D x 1.33" H		15=15W			
	7=7", 7.4"D x 1.33" H					

TRADITIONAL



WATTAGE	18W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1260	1650
Efficacy (lm/W @ 2700K, 80CRI)	70	69

MADE TO ORDER	
ORDER CODE	CATALOG NUMBER
1409610	ML2LAMTRWH18830
1409609	ML2LALTRWH24830

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2=Ceiling Flush Mounts	LA=LED Integrated	M=Medium, 13" D x 5.1"H	TR=Traditional	WH=White	[BLANK]=120V Triac dimming	18=18W	8=80CRI 9=90CRI ¹	27=2700K 30=3000K
		L=Large, 15"D x 5.2"H				24=24W		

¹ Consult factory for lead times and order quantities

PEARL



WATTAGE	16W	24W
Sourced lumen (lm @ 2700K, 80CRI)	1100	1350
Efficacy (lm/W @ 2700K, 80CRI)	69	61

MADE TO ORDER	
ORDER CODE	CATALOG NUMBER
1408700	ML2LAMPRBN16827
1408701	ML2LALPRBN22827

FAMILY	TYPE	SIZE	STYLE	FINISH	VOLTAGE	WATTAGE	CRI	CCT
ML2=Ceiling Flush Mounts	LA=LED Integrated	M=Medium, 13" D x 4.2"H	PR=Pearl	BN=Brushed Nickel	[BLANK]=120V Triac dimming	16=16W	8=80CRI 9=90CRI	27=2700K 30=3000K
		L=Large, 15"D x 4.6"H				22=22W		