

**LED HIGH OUTPUT  
NON-DIMMABLE  
OMNIDIRECTIONAL A-LAMP**  
A21 and A23 SERIES



26A23



21A21



17A21



**PRODUCT DESCRIPTION:**

MaxLite's LED High Output Non Dimmable Omnidirectional A-Line lamp replicate true A21 and A23 incandescents. They are suited to a wide variety of residential and commercial applications, including pendants, wall sconces, table and floor lamps.

**FEATURES:**

- 17W, 2,000lm, 125W Inc. replacement
- 21W, 2,600lm, 150W Inc. replacement
- 26W, 3,000-3,200lm, 200W Inc. replacement
- ENERGY STAR certified for 17W only
- 25,000 hour life (L70 standards)
- CRI: ≥ 80
- Volts: 120-277V Universal
- Suitable for damp locations

**APPLICATIONS**

- Pendants
- Table and floor lamps
- Sconces

**WARRANTY:**

5-year standard warranty (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))  
Product may be eligible for a warranty extension to 10 years, for an additional fee. Contact MaxLite for details.

**ORDERING:**

MODEL SELECTION (Full list of order codes on pg. 2)

Typical order example: 17A21ND27

MODEL SELECTION (Full list of order codes on pg. 2)		Typical order example: 17A21ND27	
FAMILY	BASE	DIMMABILITY	CCT
<b>17A21=</b> 17 watts, A21 <b>21A21=</b> 21 watts, A21 <b>26A23=</b> 26 watts, A23	(OMIT)= E26	ND= Non-Dimmable	<b>27=</b> 2700K <b>30=</b> 3000K <b>40=</b> 4000K <b>50=</b> 5000K

**SPECIFICATIONS:**

ITEM	SPECIFICATION	17A21NDxx	21A21NDxx	26A23NDxx
		DETAILS		
<b>GENERAL PERFORMANCE</b>	Power Consumption	17W	21W	26W
	Lumens Delivered	2000	2600	3,000-3,200
	Efficacy (lm/w)	118	118	116-123
	CRI	≥80		
	Color Temperature (CCT)	2700K, 3000K, 4000K, 5000K		
	Lumen Maintenance (L70)	25,000 Hours		
<b>ELECTRICAL</b>	Power Factor	≥0.95		
	Input Voltage	120-277V Universal		
<b>PHYSICAL</b>	Base Type	E26		
	Operating Temperature	-4°F - 104°F		
<b>CERTIFICATION</b>	Certification	UL Listed, Energy Star, FCC	UL Listed, FCC	
	Environment	Damp		
	Warranty	5 Year standard warranty*		

**ORDERING:**

ORDER CODE	MODEL	ENERGY STAR	WATTS	EQUIVALENCY	DELIVER LUMENS	EFFICACY (lm/W)	CRI	CCT	DIMENSIONS (W" x MOL")
<b>E26 Base</b>									
102733	17A21ND27	★	17	125W Inc.	2000	118	80	2700K	2.55" x 4.92"
102734	17A21ND30	★	17	125W Inc.	2000	118	80	3000K	
102735	17A21ND40	★	17	125W Inc.	2000	118	80	4000K	
102736	17A21ND50	★	17	125W Inc.	2000	118	80	5000K	
102729	21A21ND27		21	150W Inc.	2600	118	80	2700K	2.75" x 5.13"
102730	21A21ND30		21	150W Inc.	2600	118	80	3000K	
102731	21A21ND40		21	150W Inc.	2600	118	80	4000K	
102732	21A21ND50		21	150W Inc.	2600	118	80	5000K	
102725	26A23ND27		26	200W Inc.	3000	116	80	2700K	3.15" x 5.90"
102726	26A23ND30		26	200W Inc.	3200	123	80	3000K	
102727	26A23ND40		26	200W Inc.	3200	123	80	4000K	
102728	26A23ND50		26	200W Inc.	3200	123	80	5000K	

★ ENERGY STAR Certified

Specifications are subject to change without notice.